VALIANT
PACIFIC LLC



INTRODUCTION

Valiant Pacific LLC, 305 Al Masraf, Deira, PO Box 48679, Dubai, UAE being an associate company of **JK Tyre & Industries Limited,** is a part of one of the biggest and prestigious business organizations in India namely **'JK Organization'** which was founded over 100 years ago and is an eminent industrial group in India. Pertinently, JK Tyre & Industries Ltd. is a leading tyre manufacturer in India and amongst the top 25 manufacturers in the world with a wide range of products catering to diverse business segments in the automobile industry.

Valiant Pacific LLC is engaged in the business of trading of Automotive Tyres, Tubes, Flaps. JK Tyre & Industries Ltd has authorised Valiant Pacific LLC to trade in brand/products manufactured by it and its subsidiary namely M/s. Cavendish Industries Ltd, within the territory of Africa, Middle East and Central Asia.

Besides trading in the products/brands manufactured JK Tyre & Industries Ltd and its subsidiary M/s Cavendish Industries Ltd in the above mentioned territories, Valiant Pacific LLC is also engaged in trading of brands manufactured by approved sources of different origin under VALIANT / factory brand worldwide.




Pattern characteristic:
Specially recipe design provides tear resistance, high wear resistance, and excellent load capacity, Low rolling resistance & noise errission, excelent heat radiation, guiding stability. Excellent fuel efficiency.

Suitable conditions:
Suitable for steer/trailer position of bus and truck running on high-grade road.

LWL 6

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1054	279	3000/2725	830
12R22.5	18	9.00	152/149M	1085	289	3550/3250	930
295/80R22.5	18	9.00	152/149M	1044	298	3550/3250	900
315/80R22.5	20	9.00	157/153L	1076	310	4125/3650	860




Pattern characteristic:
Low heat generating, excellent high speed driving character, good handling quality.

Suitable conditions:

Suitable for steer/trailer position, Steer and trailer wheel, suitable for high way and good quality road use.

LUH 1

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860



Pattern characteristic:

Mixed pattern design provide strong traction and breaking power. Longer block pattern design enhance the ability of untile eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs.

Suitable conditions:

Suitable for driving wheel position, no suitable for steer position of short/middle distance trucks running on good road contiotion,

LDH 2

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860



Pattern characteristic:
High wear resistance, High cost performance.

Suitable conditions:
Suitable for trailer position of buses and light trucks running on Highway.

LUL 7

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
7.50R16LT	14	6.00G	122/118L	802	210	1500/1320	770
9.5R17.5	18	6.75	143/141M	842	240	2725/2575	930




Pattern characteristic:
Improve tread design, High wear resistance and eccentric wear resistance. Low rolling resistance, save fuel sonsumption, good handling quality.

Suitable conditions:
Steer/trailer tyre suitable for Long-distance transportation, running on high-grade road.

LUL 4

Apply Available Disable





SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1054	279	3000/2725	830
11R24.5	16	8.25	149/146M	1098	277	3250/3000	830
205/75R17.5	16	6.00	124/122M	750	213	1600/1500	750
215/75R17.5	16	6.00	126/124M	759	214	1700/1600	700
225/70R19.5	16	6.75	128/126M	812	230	1800/1700	760
235/75R17.5	16	6.75	132/130M	790	232	2000/1900	775
245/70R19.5	16	7.50	136/134M	835	252	2180/2060	830
255/70R22.5	16	7.50	140/137M	931	260	2500/2300	830
265/70R19.5	16	7.50	140/138M	862	266	2500/2360	775
275/70R22.5	16	8.25	148/145M	958	280	3150/2900	900
285/75R24.5	16	8.25	147/144L	1055	285	3075/2800	830
295/75R22.5	16	9.00	146/143L	1008	302	3000/2725	830



Pattern characteristic:
Excellent traction and draining performance, more original mileage.

Suitable conditions:
Trailer tyre of bus & Truck, not suitable for drive and steer wheel position running on well-paved roads and mixed pavements and medium/long-haul vehicles.

LTL

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
385/65R22.5	20	11.75	160K	1072	389	4500	900



Pattern characteristic:
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against treat cut.

Suitable conditions:
Suitable for all position of trucks running on non-paved roads.

LUC 3+

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900




Pattern characteristic:
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against treat cut.

Suitable conditions:
Suitable for all position of trucks running on non-paved roads.

LUC 3

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
9.00R20	16	7.00	144/142K	1018	259	2800/2650	900
10.00R20	18	7.50	149/146K	1052	278	3250/3000	930
11.00R20	18	8.00	152/149K	1085	293	3550/3250	930
12.00R20	20	8.50	156/153K	1125	315	4000/3650	900



Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction with higher original mileage, Excellent fuel efficiency.

Suitable conditions:
Suitable for all wheel position, medium/long-haul vehicles running on mixed pavements.

LUC

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
6.50R16LT	12	5.50F	110/105L	750	185	1060/925	670
7.00R16LT	14	5.50F	118/114L	775	200	1320/1180	770
7.50R16LT	14	6.00G	122/118L	805	215	1500/1320	770
8.25R16LT	16	6.50H	128/124L	855	235	1800/1600	770
8.25R20	16	6.50	139/137K	974	236	2430/2300	930
9.00R20	16	7.00	144/142K	1018	259	2800/2650	900
10.00R20	18	7.50	149/146K	1049	278	3250/3000	930
11.00R20	18	8.00	152/149K	1085	293	3550/3250	930
12.00R20	20	8.50	156/153K	1125	315	4000/3650	900
12.00R24	20	8.50	160/157K	1210	315	4500/4125	900
11R22.5	16	8.25	146/143M	1056	279	3000/2725	830
11R24.5	16	8.25	149/146M	1100	277	3250/3000	830
12R22.5	18	9.00	152/149M	1084	289	3550/3250	930
13R22.5	18	9.75	154/151L	1124	320	3750/3450	850
295/80R22.5	18	9.00	152/149M	1042	298	3550/3250	900
315/80R22.5	20	9.00	157/153L	1076	310	4125/3650	860



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.

Suitable conditions:
Suitable for all position of trucks running on non-paved roads.

LUG 4

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



Pattern characteristic:

Big deep block provice strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.

Suitable conditions:

Suitable for driving wheel position on good road condition and non-paved roads.

LDH 3

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
7.00R16LT	14	5.00F	118/114L	775	200	1320/1180	770
7.50R16LT	14	8.00G	122/118L	805	215	1500/1320	770
8.25R16LT	16	6.50L	128/124K	855	235	1800/1600	700
8.25R20	16	6.50	139/137K	972	236	2430/1600	930
11.00R20	18	8.00	152/149K	1096	293	3550/3250	930
12.00R20	20	8.50	156/153K	1136	315	4000/3650	900
12.00R24	20	8.50	160/157K	1226	315	4500/4125	900



Pattern characteristic:
Super abrasion resitance, excellent heat dissipation performance, good handling and traction with higher original mileage, Excellent fuel efficiency.

Suitable conditions:
Suitable for drive wheel position, use for mining/mountain road, medium/long haul vehicles, running on mixed pavements

LDC 4

Apply Available Disable

SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
13R22.5	18	9.75	154/151L	1124	320	3750/3450	850
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860



Pattern characteristic:

Reinforced beld and body construction enhance the loading ability, Special tread compound for high resistance against tread cut.

Suitable conditions:

Suitable for driving wheel position on good road conditions and non-paved roads.

LDC 3

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



Pattern characteristic:

Widen tread width design provides excellent driving and gripping power. Extra deep tread provides an extra poerful traction and a long tread life. Closed shoulder maintains a good irregular wear resistance. with excellent crack and tear resistance character.

Suitable conditions:

Suitable for Light, heavy duty and bus driving position on good road.

LDL

Apply Available Disable



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R24.5	16	8.25	149/146	1104	279	3250/3000	830
11R22.5	16	8.25	146/143	1054	279	3000/2725	830



Pattern characteristic:
Improved tread design, High wear resistance and sccentric wear resistance. Low rolling

Suitable conditions:
Resistance, Save fuel consumption, good handling quality
Steer/trailer tyre suitable for Long-distance transportation, running on high-grade road.

LUL

Apply Available Disable

SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143	1054	279	3000/2725	830
11R24.5	16	8.25	149/146	1104	279	3250/3000	830
295/75R22.5	16	9.00	146/143	1014	298	3000/2725	830

VALIANT
PACIFIC LLC

P.O. Box 48679 - 305, Al Masraf Tower, Baniyas Road, Dubai, UAE
Ph.: (9714) 2275122 Fax: (9714) 2275572, Email : neelabh@valiantp.com, Mobile : +971 50 5094918

VALIANT PACIFIC LLC

VALIANT

PACIFIC LLC

